

Concrete mixer bucket 1500 litres

Capacity 1.500 litres
Item number:SI1500

Technical data:

Type	Unit	SI1500
Recommended capacity	liter	1.500
Max capacity	liter	1.700
Weight (empty)	kilogram	2.200
Weight (full)	kilogram	ca. 5800
Recommended/max. oil flow	liter/minute	200/350
Continuous/max. pressure	bar	160/210
Transmission	chain	
Draininghose	hydraulic	

Equipment of our concrete mixer buckets

- 1500 litres, max. capacity 1700 litres
- Weight: approx. 2200 kg – Weight with concrete: approx. 5800 kg
- Danfoss hydraulic motor with chain drive
- Inner lining of the bucket in Steel Fe510 (S355) - thickness body: 10 mm; sides 15 mm
- Auger from HARDOX 500 – thickness: 15 mm
- Safety grid with prongs for opening the cement bags
- 6/2 valve for switching between mixing and hydraulic draining device
- Draininghose, length: 2 m
- 2 pieces hydraulic hose and socket as well as cable set

Optionally available:

- Suitable holder for carrier device
- Inner lining of the bucket in HARDOX 450 - thickness: 5 mm
- Gas spring for protective lattice incl. shut-off valve engine (lt. CE NORM)
- Diaphragm accumulator (pressure compensation for various carrier devices)

