



Concrete mixer bucket 1800 litres

Capacity 1.800 litres Item number:SI1800

Technical data:

Туре	Unit	SI1800
Recommended capacity	liter	1.800
Max capacity	liter	2.000
Weight (empty)	kilogram	2.300
Weight (full)	kilogram	ca. 6.650
Recommended/max. oil flow	liter/minute	200/350
Continuous/max. pressure	bar	160/210
Transmission	chain	
Draininghose	hydraulic	



- 1800 litres, max. capacity 2000 litres
- Weight: approx. 2300 kg Weight with concrete: approx. 6650 kg
- Danfoss hydraulic motor with chain drive
- Inner lining of the bucket in Steel Fe510 (S355) thickness body: 10 mm; sides 15 mm
- Auger from HARDOX 500 thickness: 20 mm
- Safety grid with prongs for opening the cement bags
- 6/2 valve for switching between mixing and hydraulic draining device
- Draininghose, length: 2 m
- 2 pieces hydraulic hose and socket as well as cable set

Optionally available:

- Suitable holder for carrier device
- Inner lining of the bucket in HARDOX 450 thickness: 5 mm
- Gas spring for protective lattice incl. shut-off valve engine (lt. CE NORM)
- Diaphragm accumulator (pressure compensation for various carrier devices)



