



Concrete mixer bucket 750 litres

Capacity 750 litres Item number:SI750

Technical data:

| Туре | Unit | SI750 |
|---------------------------|--------------|-----------|
| Recommended capacity | liter | 750 |
| Max capacity | liter | 800 |
| Weight (empty) | kilogram | 920 |
| Weight (full) | kilogram | ca. 2.700 |
| Recommended/max. oil flow | liter/minute | 125/240 |
| Continuous/max. pressure | bar | 180/200 |
| Transmission | chain | |
| Draininghose | hydraulic | |
| | | |



- 750 litres, max. capacity 800 litres
- Weight: approx. 920 kg Weight with concrete: approx. 2700 kg
- Danfoss hydraulic motor OMV 630 with chain drive
- Inner lining of the bucket in Steel Fe510 (S355) thickness: 10 mm
- Auger from HARDOX 500 thickness: 15 mm
- Safety grid with prongs for opening the cement bags
- 6/2 valve for switching between mixing and hydraulic draining device
- Draininghose, length: 2 m
- 2 pieces hydraulic hose and socket as well as cable set

Optionally available:

- Suitable holder for carrier device
- Inner lining of the bucket in HARDOX 450 thickness: 5 mm
- Gas spring for protective lattice incl. shut-off valve engine (lt. CE NORM)
- Diaphragm accumulator (pressure compensation for various carrier devices)







