
Concrete mixer bucket 250 litres

Capacity 250 litres
Item number:SI250



Technical data:

Type	Unit	SI250
Recommended capacity	liter	250
Max capacity	liter	300
Weight (empty)	kilogram	365
Weight (full)	kilogram	ca. 950
Recommended/max. oil flow	liter/minute	40/75
Continuous/max. pressure	bar	140/180
Transmission	chain	
Drainighose	hydraulic	



Equipment of our concrete mixer buckets

- 250 litres, max. capacity 300 litres
- Weight: approx. 365 kg – Weight with concrete: approx. 950 kg
- Danfoss hydraulic motor OMR 250 with gearbox
- Inner lining of the bucket in Steel Fe510 (S355) - thickness: 8 mm
- Auger from HARDOX 500 – thickness: 12 mm
- Safety grid with prongs for opening the cement bags
- 6/2 valve for switching between mixing and hydraulic draining device
- Drainighose, length: 2 m
- 2 pieces hydraulice hose and socket as well as cable set



Optionally available:

- Suitable holder for carrier device
- Inner lining of the bucket in HARDOX 450 - thickness: 4 mm
- Gas spring for protective lattice incl. shut-off valve engine (lt. CE NORM)
- Diaphragm accumulator (pressure compensation for various carrier devices)



HZI - Hydraulikzentrum Industriebedarf GmbH • Gewerbepark Pitztal Nr. 7 • A-6471 Arzl im Pitztal
Tel.: +43 (0)5412 / 64839 • info@hzi.at • www.hzi.at