

Concrete mixer bucket 750 litres

Capacity 750 litres
Item number: SI750

Technical data:

Type	Unit	SI750
Recommended capacity	liter	750
Max capacity	liter	800
Weight (empty)	kilogram	920
Weight (full)	kilogram	ca. 2.700
Recommended/max. oil flow	liter/minute	125/240
Continuous/max. pressure	bar	180/200
Transmission	chain	
Draininghose	hydraulic	

Equipment of our concrete mixer buckets

- 750 litres, max. capacity 800 litres
- Weight: approx. 920 kg – Weight with concrete: approx. 2700 kg
- Danfoss hydraulic motor OMV 630 with chain drive
- Inner lining of the bucket in Steel Fe510 (S355) - thickness: 10 mm
- Auger from HARDOX 500 – thickness: 15 mm
- Safety grid with prongs for opening the cement bags
- 6/2 valve for switching between mixing and hydraulic draining device
- Draininghose, length: 2 m
- 2 pieces hydraulic hose and socket as well as cable set

Optionally available:

- Suitable holder for carrier device
- Inner lining of the bucket in HARDOX 450 - thickness: 5 mm
- Gas spring for protective lattice incl. shut-off valve engine (lt. CE NORM)
- Diaphragm accumulator (pressure compensation for various carrier devices)

